DART SERVICE INSTRUCTION
TO AMEND INSTALLATION INSTRUCTIONS D204-635 REV. G AND LATER APPROVED REVISIONS AND

INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D204-635 REV 4 AND LATER APPROVED REVISIONS

REF CANADIAN STC: SH96-88 REF FAA STC: SR00563NY REF EASA STC: EASA.IM.R.S.01303

## 1.0 PURPOSE

For D204-635-041 at CHG 006 or later, D204-635-011 at CHG 011 or later, the rubber gaskets that are installed between the wearshoes and the bottom of the skidtube have been replaced with a textured coating. This change facilitates wearshoe installation and prolongs the life of the wearshoes. The D3564-X wearshoes with textured coating may be installed on skidtubes at earlier change numbers and no longer require installation of the D3566-X rubber gaskets. This service instruction also introduces the D204-635-043 Replacement Wearshoe Kit for customer convenience.

## 2.0 INSTALLATION

See Figure 1 of this Service Instruction for installation of the wearshoes on the D204-635-041 at CHG 006 or later, and D204-635-011 at CHG 011 or later. The parts list in Section 5.0 of Installation Instructions D204-635 and Section 32.10 of the Instructions for Continued Airworthiness ICA-D204-635 is updated as follows.

### 3.0 UPDATED PARTS LIST

IS:

Item	635 -011	635 -041	641 -011	Part Number	Description
6A		1		D3564-9	* WEARSHOE (REPLACES D2577-1)
7A		1		D3564-11	* WEARSHOE (REPLACES D2577-3)
8A		1		D3564-7	* WEARSHOE (REPLACES D2577-7)
9A		1		D3564-13	*WEARSHOE

#### WAS:

Item	635 -011	635 -041	641 -011	Part Number	Description
- CA	-011	<del>-v</del> -	-011	Hace a co	*14/F4501/05/05F01 6050 50555 4
<u>6A</u>		<u> </u>		D3564-9	* WEARSHOE (REPLACES D2577-1)
6B		1		D3566-1	* GASKET
7A		1		D3564-11	* WEARSHOE (REPLACES D2577-3)
7B		1		D3566-1	* GASKET
8A		1		D3564-7	* WEARSHOE (REPLACES D2577-7)
8B		1		D3566-7	* GASKET
9A		1		D3564-13	* WEARSHOE
9B		1		D3566-13	* GASKET




Figure 1

CANADA **DEPARTMENT OF TRANSPORT AIRCRAFT CERTIFICATION BRANCH** DAO # 01-O-01

D. SHEPHERD (DE # 02)

DATE: CERT. NO.: SH96-88 **ISSUE NO.:** 

	Α	NEW IS	SUE	
	REV.			)[
	DESIGN	Į.	SAD	Γ
***************************************	DRAWN	Į	SAD	
***************************************	CHECK	ED	ZF	
***************************************	MFG. A	PPR.	N/A	
	APPRO	VED	NO "	1
	DE APP	R.	D8-//-	'
	DATE	18.1	2.18	

APPROVED

NEW IS	SUE		SAD	18.12.18		
	ſ	DESCRIPTION	BY	DATE		
	SAD	DART AEROSPA	CEL	EITD		
	SAD	HAWKESBURY, ONTARI				
D	ZF	DRAWING NO.		REV. A		
PR.	N/A	DSI 9782		SHEET 1 OF 2		
/ED	NO "	TITLE		SCALE		
R.	D9-//-	WEARSHOE INSTALI	_ATIC	N NTS		
18.1	2.18	COPYRIGHT © 2018 BY DART THIS DOCUMENT IS PRIVATE AND CONFERENTAL AND IS SUPPLE NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMANIS WRITTEN PERMISSION FROM DART AL	DON'THE EXPRE CATED TO ANY D	ES CONDITION THAT IT IS		

0.0

40 40 40

## **4.0 REPLACEMENT WEARSHOE KIT**

Item	635 -043	Part Number	Description
	Х	D204-635-043	REPLACEMENT WEARSHOE KIT
1	1	D3564-7	* WEARSHOE (REPLACES D2577-7)
2	1	D3564-9	* WEARSHOE (REPLACES D2577-1)
3	1	D3564-11	* WEARSHOE (REPLACES D2577-3)
4	1	D3564-13	* WEARSHOE
5	44	AN3C4A	* BOLT (REPLACES AN3-4A)
6	44	NAS1149C0332R	*WASHER (AN960C10L)

## 5.0 WEARSHOE REMOVAL/ REPLACEMENT

- 5.1 Remove D3564-7/-9/-11/-13 wearshoes by removing AN3C4A bolts and NAS1149C0332R washers.
- 5.2 Inspect wearshoes for serviceability per ICA-D204-635 section 5.2.2 and replace if required.
- 5.3 If present, clean residual sealant off the bottom of the skidtube. Check for skidtube corrosion and mechanical damage in accordance with ICA-D204-635 Chapter 5 and repair as required. Inspect the condition of the Rockguard 4714A sealant on the wearshoes. If damaged, remove using an abrasive pad. Apply a new layer of Rockguard 4714A sealant (0.020" 0.040" thick) (0.5 1.0 mm thick) and allow to cure per Manufacturer's Instructions.
- **5.4** Install D3564-7/-9/-11/-13 using AN3C4A bolts and NAS1149C0332R washers. Torque AN3 bolts to 20 to 25-lb (2-3 N-m)

# 6.0 WEIGHT AND BALANCE

There is negligible weight and balance change associated with this modification

DESIGN	SAD	DART AEROSPACE LTD	
DRAWN	SAD	HAWKESBURY, ONTARIO, CANADA	
CHECKED	ZF	DRAWING NO.	REV. A
MFG. APPR.	N/A	DSI 9782 <sub>SHE</sub>	ET 2 OF 2
APPROVED	NO 📈	TITLE	SCALE
DE APPR.	D\$=/	WEARSHOE INSTALLATION	NTS
DATE 18.1	2.18	THIS DOCUMENT IS PRIVATE AND CONFERENTIAL AND IS SUPPLIED ON THE EXPRESS COM- NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PER WANTEN PERMISSION FROM DAYS DRYSPAGE LTD.	DITION THAT IT IS